HOUSE BILL NO. 74

INTRODUCED BY GOULD

BY REQUEST OF THE ATTORNEY GENERAL

IN THE HOUSE

January 4, 1979	Introduced and referred to Committee on Highways and Transportation.
January 6, 1979	On motion joint rule 6-6 suspended and sponsor's signature allowed to be added to Pre-Filed bill.
January 18, 1979	Committee recommend bill do pass and be placed on Consent Calendar. Report adopted.
January 19, 1979	Printed and placed on members' desks.
January 22, 1979	Third Reading Consent Calendar passed. Transmitted to Second House.
IN THE SENATE	
January 23, 1979	Introduced and referred to Committee on Highways and Transportation.
February 5, 1979	Committee recommend bill be concurred in. Report adopted.
February 7, 1979	Second Reading, concurred in.
February 9, 1979	Third Reading, concurred in.

IN THE HOUSE

February 10, 1979

Returned from Second House. Concurred in.

Sent to enrolling.
Reported correctly enrolled.

	BOUSE BILL NO. 18
:	INTRODUCED BY
ı	BY REQUEST OF THE ATTORNEY GENERAL

A BILL FOR AN ACT ENTITLED: "AN ACT TO AMEND SECTIONS 51-9-204 AMD 61-9-205 TO DECREASE THE MINIMUM HEIGHT REQUIREMENT FOR TAILLAMPS AND REPLECTORS FROM 20 INCHES TO 15 INCHES TO COMPORM TO FEDERAL REGULATIONS."

THE IT CHARTED BY THE LEGISLATURE OF THE STATE OF MONTANA!

Section 1. Section 61-9-204. MCA, is assended to read:

**61-9-204. Taillamps. (1) Every motor vehicle.

trailer, semitrailer, and pole trailer and any other vehicle.

which is being drawn at the end of a train of vehicles shall be equipped with at least one taillamp acunted on the rear, which, when lighted as hereinbefore required, shall emit a read light plainly visible from a distance of 500 feet to the rear, provided that in the case of a train of vehicles only the taillamp on the rearmost vehicle need actually be seen from the distance specified. Further, overy such above—mentionad wehicle, other than a truck tractor, registered in this state and manufactured or assembled after January 1, 1956, shall be equipped with at least two required, shall comply with the precisions of this section.

- 1 (2) Every taillamp upon every vehicle shall be located
 2 at a height of not more than 72 inches or less than 28 15
 3 inches...
 - (3) Either taillamp or a separate lamp shall be so constructed and placed as to illuminate with a white light the rear registration plate and render it clearly legible from a distance of 50 feet to the rear. Any taillamp or taillamps together with any separate lamp for illuminating the rear registration plate, shall be so wired as to be lighted whenever the headlamps or auxiliary driving lamps are lighted.
 - Section 20 Section 61-9-205. MCA, is amended to reads #61-9-205. New motor vehicles to be equipped with reflectors. (1) Every new motor vehicle hereafter sold and operated upon a highway, other than a truck tractor, shall carry on the rear, either as a part of the taillamps or separately, two red reflectors, except that every motorcycle and motor-driven cycle shall carry at least one reflector meeting the requirements of this suction, and except that vehicles of the type mentioned in 61-9-208 shall be equipped with reflectors as required in those sections applicable thereto.
 - (2) Every such roffector shall be counted on the vehicle at a height not less than 28 15 inches or more than 60 inches measured as not forth in 61-9-202121 and shall be

of such size and characteristics and so mounted as to be
visible at night from all distances within 300 feet to 50
feet from such vehicle when directly in front of lawful
upper beams of headlamps, except that visibility from a
greater distance is——hereinofter may be required of
reflectors on certain types of vehicles.**

-End-

1

2

3

12

13

14

15

15

17

18

19

20

21

22

23

24

25

4

9

10

11

12

13

14 15

16

17

18

19

20

21

22

23

24

25

Approved by Committee on Highways & Transportation

1	HOUSE BILL NO. 74
2	INTRODUCED BY GOULD
3	BY REQUEST OF THE ATTORNEY GENERAL

5 A BILL FOR AN ACT ENTITLED: "AN ACT TO AMEND SECTIONS
6 61-9-204 AND 61-9-205 TO DECREASE THE MINIMUM HEIGHT
7 REQUIREMENT FOR TAILLAMPS AND REFLECTORS FROM 20 INCHES TO
8 15 INCHES TO COMFORM TO FEDERAL REGULATIONS."

BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA:

Section 1. Section 61-9-204. MCA. is amended to read: *61-9-204. Taillamps. (1) Every motor vehicle. trailer, semitrailer, and pole trailer and any other vehicle which is being drawn at the end of a train of vehicles shall be equipped with at least one taillamp mounted on the rear. which, when lighted as hereinbefore required, shall emit a red light plainly visible from a distance of 500 feet to the rear, provided that in the case of a train of vehicles only the taillamp on the rearmost vehicle need actually be seen the distance specified. Further, everv above-mentioned vehicle, other than a truck tractor, registered in this state and manufactured or assembled after January 1, 1956, shall be equipped with at least two taillamps mounted on the rear: which when lighted as herein required, shall comply with the provisions of this section.

- (2) Every taillamp upon every vehicle shall be located at a height of not more than 72 inches or less than $\frac{20}{15}$ inches.
- 4 (3) Either taillamp or a separate lamp shall be so constructed and placed as to illuminate with a white light 6 the rear registration plate and render it clearly legible 7 from a distance of 50 feet to the rear. Any taillamp or 8 taillamps, together with any separate lamp for illuminating 9 the rear registration plate, shall be so wired as to be 10 lighted whenever the headlamps or auxiliary driving lamps are lighted.**
 - Section 2. Section 61-9-205, MCA, is amended to read:

 #61-9-205. New motor vehicles to be equipped with
 reflectors. (1) Every new motor vehicle hereafter sold and
 operated upon a highway, other than a truck tractor, shall
 carry on the rear, either as a part of the taillamps or
 separately, two red reflectors, except that every motorcycle
 and motor-driven cycle shall carry at least one reflector
 meeting the requirements of this section, and except that
 vehicles of the type mentioned in 61-9-208 shall be equipped
 with reflectors as required in those sections applicable
 thereto.
 - (2) Every such reflector shall be mounted on the vehicle at a height not less than 20 15 inches or more than 50 inches measured as set forth in 61-9-202(2) and shall be

HB 0074/02

- 1 of such size and characteristics and so mounted as to be
- 2 visible at night from all distances within 300 feet to 50
- 3 feet from such vehicle when directly in front of lawful
- 4 upper beams of headlamps, except that visibility from a
- greater distance is---hereinafter <u>may be</u> required of
- reflectors on certain types of vehicles.*

-End-

HB 74

-3-

HB 0074/03

46th Legislature

HB 0074/03

1	HOUSE BILL NO. 74
2	INTRODUCED BY GOULD
3	BY REQUEST OF THE ATTORNEY GENERAL

A BILL FOR AN ACT ENTITLED: "AN ACT TO AMEND SECTIONS 61-9-204 AND 61-9-205 TO DECREASE THE MINIMUM HEIGHT REQUIREMENT FOR TAILLAMPS AND REFLECTORS FROM 20 INCHES TO 15 INCHES TO COMFORM TO FEDERAL REGULATIONS."

BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA:

Section 1. Section 61-9-204, MCA, is amended to read:

**61-9-204. Taillamps. (1) Every motor vehicle.

trailer, semitrailer, and pole trailer and any other vehicle which is being drawn at the end of a train of vehicles shall be equipped with at least one taillamp mounted on the rear, which, when lighted as hereinbefore required, shall emit a red light plainly visible from a distance of 500 feet to the rear, provided that in the case of a train of vehicles only the taillamp on the rearmost vehicle need actually be seen from the distance specified. Further, every such above-mentioned vehicle, other than a truck tractor, registered in this state and manufactured or assembled after January 1, 1956, shall be equipped with at least two taillamps mounted on the rear, which when lighted as herein required, shall comply with the provisions of this section.

- 1 (2) Every taillamp upon every vehicle shall be located
 2 at a height of not more than 72 inches or less than 20 15
 3 inches.
- 4 (3) Either taillamp or a separate lamp shall be so
 5 constructed and placed as to illuminate with a white light
 6 the rear registration plate and render it clearly legible
 7 from a distance of 50 feet to the rear. Any taillamp or
 8 taillamps, together with any separate lamp for illuminating
 9, the rear registration plate, shall be so wired as to be
 10 lighted whenever the headlamps or auxiliary driving lamps
 11 are lighted.**
 - Section 2. Section 61-9-205, MCA, is amended to read:

 "61-9-205. New motor vehicles to be equipped with
 reflectors. (1) Every new motor vehicle hereafter sold and
 operated upon a highway, other than a truck tractor, shall
 carry on the rear, either as a part of the taillamps or
 separately, two red reflectors, except that every motorcycle
 and motor-driven cycle shall carry at least one reflector
 meeting the requirements of this section, and except that
 vehicles of the type mentioned in 61-9-208 shall be equipped
 with reflectors as required in those sections applicable
 thereto.
- 23 (2) Every such reflector shall be mounted on the 24 vehicle at a height not less than 20 15 inches or more than 25 60 inches measured as set forth in 61-9-202(2) and shall be

- 1 of such size and characteristics and so mounted as to be
- 2 visible at night from all distances within 300 feet to 50
- 3 feet from such vehicle when directly in front of lawful
- 4 upper beams of headlamps, except that visibility from a
- 5 greater distance is---hereinofter may be required of
- 6 reflectors on certain types of vehicles.**

-End-

HB 74