- SB 166 INTRODUCED BY MCCALLUM REQUIRING FLAPS OR ANTISAIL FLAPS ON REAR WHEELS OF ALL VEHICLES
 - 1/21 INTRODUCED
 - 1/21 REFERRED TO HIGHWAYS & TRANSPORTATION

.

•

2/03 HEARING

.

2/05 TABLED IN COMMITTEE

50th Legislature

LC 1255/01

Alrate BILL NO. 166 INTRODUCED BY Michalling 1 2 3 A BILL FOR AN ACT ENTITLED: "AN ACT REQUIRING FLAPS OR Λ ANTISALL FLAPS ON THE REAR WHEELS OF ALL VEHICLES: AND 5 AMENDING SECTION 61-9-407, MCA." 6 7 BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA: 8 Section 1. Section 61-9-407, MCA, is amended to read: q "61-9-407. Fenders, splash aprons, or flaps, or 10 antisail flaps required on certain vehicles -- dimension and 11 location. (1) It shall-be is unlawful for any person to 12 13 move, or permit to be moved, any truck--busy--truck-tractor 14 motor vehicle, trailer, or semitrailer, as defined in this 15 title, upon the public highways without having first equipped the rearmost wheels or set of wheels of such the 16 17 vehicle: (a) if the vehicle is an automobile, with fenders, and 18 19 splash aprons; or flaps; (b) if the vehicle is a truck of rated capacity of 20 21 1 1/2 tons or less, with splash aprons or flaps; or 22 (c) if the vehicle is a truck of more than $1 \frac{1}{2}$ tons 23 rated capacity or a bus, truck tractor, trailer, or 24 semitrailer, with antisail flaps. 25 (2) Such fenders, splash aprons, or flaps, or antisail

LC 1255/01-

<u>flaps</u> shall must be designed, constructed, and attached to
 the vehicle in such manner so as to arrest and deflect dirt,
 mud, water, rocks, and other substances which may be picked
 up by the rear wheels of such the vehicle and thrown into
 the air, as follows:
 (a) If the vehicle is equipped with fenders, the same

7 shall <u>must</u> extend in full width from a point above and
8 forward of the center of the tire or tires over and to the
9 rear thereof.

(b) If the vehicle is equipped with splash aprons, or
flaps, or antisail flaps, the same shall must extend
downward in full width from a point not lower than halfway
between the center of the tire or tires and the top of said
tire or tires and to the rear thereof.

(c) If the vehicle is in excess of 8,000 pounds gross vehicle weight, such fenders, splash aprons, or flaps, or antisail flaps shall must extend downward to a point that is not more than 10 inches above the surface of the highway when the vehicle is empty.

(d) If the vehicle is 8,000 pounds or less gross
vehicle weight such fenders, splash aprons, or flaps, or
antisail flaps shall must extend downward to a point that is
not more than 20 inches above the surface of the highway
when the vehicle is empty.

25 t2;(3) Fenders, splash aprons, or flaps, or antisail

-2-

INTRODUCED BILL

58-166



1 <u>flaps</u>, as used in subsection <u>subsections</u> (1) <u>and (2)</u> of this 2 section, <u>shall</u>--be--deemed-to-be <u>are</u> of sufficient size and 3 construction as to comply with the requirements thereof, if 4 constructed as follows:

5 (a) when measured on the cross-sections of the tread 6 of the wheel or on the combined cross-sections of the treads 7 of multiple wheels, such the fender, splash apron, or flap, 8 or antisail flap extends at least to each side of the width 9 of the tire or of the combined width of the multiple tires, 10 as the case may be; and

11 (b) such the fender, splash apron, or flap, or 12 antisail flap is so constructed as to be capable at all 13 times of arresting and deflecting such dirt, mud, water, or 14 other substance as may be picked up and carried by such 15 wheel or wheels."

16 <u>NEW SECTION.</u> Section 2. Extension of authority. Any
17 existing authority of the department of justice to make
18 rules on the subject of the provisions of this act is
19 extended to the provisions of this act.

-End-

-3-