

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30

SENATE BILL NO. 283

INTRODUCED BY Dalton

A BILL FOR AN ACT ENTITLED: "AN ACT REVISING THE TYPE OF VEHICLE COMBINATION USED FOR HAULING RAW LOGS THAT IS SUBJECT TO LENGTH RESTRICTIONS; AND AMENDING SECTION 61-10-104, MCA."

BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA:

Section 1. Section 61-10-104, MCA, is amended to read:

"61-10-104. Length -- definitions. (1) A single truck, bus, or any self-propelled vehicle, unladen or with load, may not have an overall length, inclusive of front and rear bumpers, in excess of 45 feet.

(2) (a) When used in a truck tractor-semitrailer combination, the semitrailer may not exceed 53 feet in length, excluding those portions not designed to carry a load, except as provided by 61-10-124. When used in a truck tractor-semitrailer-trailer or a truck tractor-semitrailer-semitrailer combination, the semitrailer and trailer or the two semitrailers may not exceed 28 1/2 feet each in length, excluding those portions not designed to carry a load, except as provided by 61-10-124. Truck tractor-semitrailer, truck tractor-semitrailer-trailer, and truck tractor-semitrailer-semitrailer combinations are not subject to a combination length limit.

(b) A stinger-steered automobile or boat transporter may not exceed 75 feet in length plus a maximum 3 feet of front overhang and 4 feet of rear overhang, except as provided by 61-10-124. "Stinger-steered automobile or boat transporter" means a truck tractor-semitrailer combination that has a fifth wheel on a drop frame located behind and below the rear axle of the truck tractor and that is designed and used for the transportation of vehicles or assembled boats or boat hulls.

(c) All other combinations of vehicles may not have a combination length in excess of 75 feet, except as provided by 61-10-124. If the combination consists of more than two units, the rear units of the combination must be equipped with breakaway brakes.

(3) A motor vehicle may not tow more than one motor vehicle, and a motor vehicle may not draw more than three motor vehicles attached to it by the triple saddle-mount method (that is, by mounting the front wheels of one vehicle on the bed of another, leaving only the rear wheels of the vehicle in contact

1 with the roadway), nor may this combination have a combination length in excess of 75 feet.

2 (4) A passenger vehicle or truck of less than 2,000 pounds "manufacturers' rated capacity" may
3 not tow more than one trailer or semitrailer, nor may this combination have a length in excess of 65 feet.

4 (5) (a) The length of a vehicle combination consisting of a truck or truck-tractor and one ~~trailer,~~
5 pole trailer, or semitrailer hauling raw logs may not exceed 75 feet in overall length. As used in this
6 subsection (a), the term "length" means the total length of the vehicle combination beginning at the front
7 of the front bumper of the truck or truck-tractor and extending to the most distant end of the logs being
8 hauled. A term permit for an overlength vehicle combination, as provided in 61-10-124(3), does not apply
9 to the vehicle combination described in this subsection (a). A vehicle combination exceeding 75 feet must
10 have a trip permit.

11 (b) The maximum overhang of any log may not exceed 15 feet, except by special, single-trip
12 permit. Overhang is measured from the center of the rear-most axle to the most distant end of the logs
13 being hauled.

14 (c) The provisions in subsections (5)(a) and (5)(b) do not apply to a vehicle combination hauling
15 utility poles.

16 (6) As used in this chapter, the following definitions apply:

17 (a) "Combination length" means the total length of a combination of vehicles, such as a truck
18 tractor-semitrailer-trailer combination, measured from the front bumper of the motor vehicle to the back
19 bumper or rear extremity of the last trailer, including the connection tongues.

20 (b) "Combined trailer length" means the total length of a combination of trailers measured from the
21 front of the first trailer to the back of the last trailer, including the connection tongues and loads.

22 (c) "Length", except as provided in subsection (5)(a), means the total longitudinal dimension of a
23 single vehicle, a trailer, or a semitrailer. The length of a trailer or semitrailer is measured from the front of
24 the cargo-carrying unit to its rear, exclusive of safety or energy efficiency devices, air-conditioning units,
25 air compressors, flexible fender extensions, splash and spray suppressant devices, bolsters, mechanical
26 fastening devices, and hydraulic lift gates.

27 (d) "Rocky Mountain double" means a combination of vehicles that includes a truck tractor pulling
28 a long semitrailer and a shorter trailer."

29 -END-

APPROVED BY COM ON
HIGHWAYS & TRANSPORTATION

SENATE BILL NO. 283

INTRODUCED BY *Dalton*

A BILL FOR AN ACT ENTITLED: "AN ACT REVISING THE TYPE OF VEHICLE COMBINATION USED FOR HAULING RAW LOGS THAT IS SUBJECT TO LENGTH RESTRICTIONS; AND AMENDING SECTION 61-10-104, MCA."

BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA:

Section 1. Section 61-10-104, MCA, is amended to read:

"61-10-104. Length -- definitions. (1) A single truck, bus, or any self-propelled vehicle, unladen or with load, may not have an overall length, inclusive of front and rear bumpers, in excess of 45 feet.

(2) (a) When used in a truck tractor-semitrailer combination, the semitrailer may not exceed 53 feet in length, excluding those portions not designed to carry a load, except as provided by 61-10-124. When used in a truck tractor-semitrailer-trailer or a truck tractor-semitrailer-semitrailer combination, the semitrailer and trailer or the two semitrailers may not exceed 28 1/2 feet each in length, excluding those portions not designed to carry a load, except as provided by 61-10-124. Truck tractor-semitrailer, truck tractor-semitrailer-trailer, and truck tractor-semitrailer-semitrailer combinations are not subject to a combination length limit.

(b) A stinger-steered automobile or boat transporter may not exceed 75 feet in length plus a maximum 3 feet of front overhang and 4 feet of rear overhang, except as provided by 61-10-124. "Stinger-steered automobile or boat transporter" means a truck tractor-semitrailer combination that has a fifth wheel on a drop frame located behind and below the rear axle of the truck tractor and that is designed and used for the transportation of vehicles or assembled boats or boat hulls.

(c) All other combinations of vehicles may not have a combination length in excess of 75 feet, except as provided by 61-10-124. If the combination consists of more than two units, the rear units of the combination must be equipped with breakaway brakes.

(3) A motor vehicle may not tow more than one motor vehicle, and a motor vehicle may not draw more than three motor vehicles attached to it by the triple saddle-mount method (that is, by mounting the front wheels of one vehicle on the bed of another, leaving only the rear wheels of the vehicle in contact

1 with the roadway), nor may this combination have a combination length in excess of 75 feet.

2 (4) A passenger vehicle or truck of less than 2,000 pounds "manufacturers' rated capacity" may
3 not tow more than one trailer or semitrailer, nor may this combination have a length in excess of 65 feet.

4 (5) (a) The length of a vehicle combination consisting of a truck or truck-tractor and one ~~trailer,~~
5 pole trailer, or semitrailer hauling raw logs may not exceed 75 feet in overall length. As used in this
6 subsection (a), the term "length" means the total length of the vehicle combination beginning at the front
7 of the front bumper of the truck or truck-tractor and extending to the most distant end of the logs being
8 hauled. A term permit for an overlength vehicle combination, as provided in 61-10-124(3), does not apply
9 to the vehicle combination described in this subsection (a). A vehicle combination exceeding 75 feet must
10 have a trip permit.

11 (b) The maximum overhang of any log may not exceed 15 feet, except by special, single-trip
12 permit. Overhang is measured from the center of the rear-most axle to the most distant end of the logs
13 being hauled.

14 (c) The provisions in subsections (5)(a) and (5)(b) do not apply to a vehicle combination hauling
15 utility poles.

16 (6) As used in this chapter, the following definitions apply:

17 (a) "Combination length" means the total length of a combination of vehicles, such as a truck
18 tractor-semitrailer-trailer combination, measured from the front bumper of the motor vehicle to the back
19 bumper or rear extremity of the last trailer, including the connection tongues.

20 (b) "Combined trailer length" means the total length of a combination of trailers measured from the
21 front of the first trailer to the back of the last trailer, including the connection tongues and loads.

22 (c) "Length", except as provided in subsection (5)(a), means the total longitudinal dimension of a
23 single vehicle, a trailer, or a semitrailer. The length of a trailer or semitrailer is measured from the front of
24 the cargo-carrying unit to its rear, exclusive of safety or energy efficiency devices, air-conditioning units,
25 air compressors, flexible fender extensions, splash and spray suppressant devices, bolsters, mechanical
26 fastening devices, and hydraulic lift gates.

27 (d) "Rocky Mountain double" means a combination of vehicles that includes a truck tractor pulling
28 a long semitrailer and a shorter trailer."

29

-END-

SENATE BILL NO. 283

INTRODUCED BY

Quabro

A BILL FOR AN ACT ENTITLED: "AN ACT REVISING THE TYPE OF VEHICLE COMBINATION USED FOR HAULING RAW LOGS THAT IS SUBJECT TO LENGTH RESTRICTIONS; AND AMENDING SECTION 61-10-104, MCA."

BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA:

Section 1. Section 61-10-104, MCA, is amended to read:

"61-10-104. Length -- definitions. (1) A single truck, bus, or any self-propelled vehicle, unladen or with load, may not have an overall length, inclusive of front and rear bumpers, in excess of 45 feet.

(2) (a) When used in a truck tractor-semitrailer combination, the semitrailer may not exceed 53 feet in length, excluding those portions not designed to carry a load, except as provided by 61-10-124. When used in a truck tractor-semitrailer-trailer or a truck tractor-semitrailer-semitrailer combination, the semitrailer and trailer or the two semitrailers may not exceed 28 1/2 feet each in length, excluding those portions not designed to carry a load, except as provided by 61-10-124. Truck tractor-semitrailer, truck tractor-semitrailer-trailer, and truck tractor-semitrailer-semitrailer combinations are not subject to a combination length limit.

(b) A stinger-steered automobile or boat transporter may not exceed 75 feet in length plus a maximum 3 feet of front overhang and 4 feet of rear overhang, except as provided by 61-10-124. "Stinger-steered automobile or boat transporter" means a truck tractor-semitrailer combination that has a fifth wheel on a drop frame located behind and below the rear axle of the truck tractor and that is designed and used for the transportation of vehicles or assembled boats or boat hulls.

(c) All other combinations of vehicles may not have a combination length in excess of 75 feet, except as provided by 61-10-124. If the combination consists of more than two units, the rear units of the combination must be equipped with breakaway brakes.

(3) A motor vehicle may not tow more than one motor vehicle, and a motor vehicle may not draw more than three motor vehicles attached to it by the triple saddle-mount method (that is, by mounting the front wheels of one vehicle on the bed of another, leaving only the rear wheels of the vehicle in contact

1 with the roadway), nor may this combination have a combination length in excess of 75 feet.

2 (4) A passenger vehicle or truck of less than 2,000 pounds "manufacturers' rated capacity" may
3 not tow more than one trailer or semitrailer, nor may this combination have a length in excess of 65 feet.

4 (5) (a) The length of a vehicle combination consisting of a truck or truck-tractor and one ~~trailer,~~
5 pole trailer, or semitrailer hauling raw logs may not exceed 75 feet in overall length. As used in this
6 subsection (a), the term "length" means the total length of the vehicle combination beginning at the front
7 of the front bumper of the truck or truck-tractor and extending to the most distant end of the logs being
8 hauled. A term permit for an overlength vehicle combination, as provided in 61-10-124(3), does not apply
9 to the vehicle combination described in this subsection (a). A vehicle combination exceeding 75 feet must
10 have a trip permit.

11 (b) The maximum overhang of any log may not exceed 15 feet, except by special, single-trip
12 permit. Overhang is measured from the center of the rear-most axle to the most distant end of the logs
13 being hauled.

14 (c) The provisions in subsections (5)(a) and (5)(b) do not apply to a vehicle combination hauling
15 utility poles.

16 (6) As used in this chapter, the following definitions apply:

17 (a) "Combination length" means the total length of a combination of vehicles, such as a truck
18 tractor-semitrailer-trailer combination, measured from the front bumper of the motor vehicle to the back
19 bumper or rear extremity of the last trailer, including the connection tongues.

20 (b) "Combined trailer length" means the total length of a combination of trailers measured from the
21 front of the first trailer to the back of the last trailer, including the connection tongues and loads.

22 (c) "Length", except as provided in subsection (5)(a), means the total longitudinal dimension of a
23 single vehicle, a trailer, or a semitrailer. The length of a trailer or semitrailer is measured from the front of
24 the cargo-carrying unit to its rear, exclusive of safety or energy efficiency devices, air-conditioning units,
25 air compressors, flexible fender extensions, splash and spray suppressant devices, bolsters, mechanical
26 fastening devices, and hydraulic lift gates.

27 (d) "Rocky Mountain double" means a combination of vehicles that includes a truck tractor pulling
28 a long semitrailer and a shorter trailer."

29

-END-

1 SENATE BILL NO. 283

2 INTRODUCED BY JABS

3
4 A BILL FOR AN ACT ENTITLED: "AN ACT REVISING THE TYPE OF VEHICLE COMBINATION USED FOR
5 HAULING RAW LOGS THAT IS SUBJECT TO LENGTH RESTRICTIONS; AND AMENDING SECTION
6 61-10-104, MCA."
7

8 BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA:
9

10 Section 1. Section 61-10-104, MCA, is amended to read:

11 "61-10-104. Length -- definitions. (1) A single truck, bus, or any self-propelled vehicle, unladen
12 or with load, may not have an overall length, inclusive of front and rear bumpers, in excess of 45 feet.

13 (2) (a) When used in a truck tractor-semitrailer combination, the semitrailer may not exceed 53 feet
14 in length, excluding those portions not designed to carry a load, except as provided by 61-10-124. When
15 used in a truck tractor-semitrailer-trailer or a truck tractor-semitrailer-semitrailer combination, the semitrailer
16 and trailer or the two semitrailers may not exceed 28 1/2 feet each in length, excluding those portions not
17 designed to carry a load, except as provided by 61-10-124. Truck tractor-semitrailer, truck
18 tractor-semitrailer-trailer, and truck tractor-semitrailer-semitrailer combinations are not subject to a
19 combination length limit.

20 (b) A stinger-steered automobile or boat transporter may not exceed 75 feet in length plus a
21 maximum 3 feet of front overhang and 4 feet of rear overhang, except as provided by 61-10-124.
22 "Stinger-steered automobile or boat transporter" means a truck tractor-semitrailer combination that has a
23 fifth wheel on a drop frame located behind and below the rear axle of the truck tractor and that is designed
24 and used for the transportation of vehicles or assembled boats or boat hulls.

25 (c) All other combinations of vehicles may not have a combination length in excess of 75 feet,
26 except as provided by 61-10-124. If the combination consists of more than two units, the rear units of the
27 combination must be equipped with breakaway brakes.

28 (3) A motor vehicle may not tow more than one motor vehicle, and a motor vehicle may not draw
29 more than three motor vehicles attached to it by the triple saddle-mount method (that is, by mounting the
30 front wheels of one vehicle on the bed of another, leaving only the rear wheels of the vehicle in contact

1 with the roadway), nor may this combination have a combination length in excess of 75 feet.

2 (4) A passenger vehicle or truck of less than 2,000 pounds "manufacturers' rated capacity" may
3 not tow more than one trailer or semitrailer, nor may this combination have a length in excess of 65 feet.

4 (5) (a) The length of a vehicle combination consisting of a truck or truck-tractor and one trailer,
5 pole trailer, or semitrailer hauling raw logs may not exceed 75 feet in overall length. As used in this
6 subsection (a), the term "length" means the total length of the vehicle combination beginning at the front
7 of the front bumper of the truck or truck-tractor and extending to the most distant end of the logs being
8 hauled. A term permit for an overlength vehicle combination, as provided in 61-10-124(3), does not apply
9 to the vehicle combination described in this subsection (a). A vehicle combination exceeding 75 feet must
10 have a trip permit.

11 (b) The maximum overhang of any log may not exceed 15 feet, except by special, single-trip
12 permit. Overhang is measured from the center of the rear-most axle to the most distant end of the logs
13 being hauled.

14 (c) The provisions in subsections (5)(a) and (5)(b) do not apply to a vehicle combination hauling
15 utility poles.

16 (6) As used in this chapter, the following definitions apply:

17 (a) "Combination length" means the total length of a combination of vehicles, such as a truck
18 tractor-semitrailer-trailer combination, measured from the front bumper of the motor vehicle to the back
19 bumper or rear extremity of the last trailer, including the connection tongues.

20 (b) "Combined trailer length" means the total length of a combination of trailers measured from the
21 front of the first trailer to the back of the last trailer, including the connection tongues and loads.

22 (c) "Length", except as provided in subsection (5)(a), means the total longitudinal dimension of a
23 single vehicle, a trailer, or a semitrailer. The length of a trailer or semitrailer is measured from the front of
24 the cargo-carrying unit to its rear, exclusive of safety or energy efficiency devices, air-conditioning units,
25 air compressors, flexible fender extensions, splash and spray suppressant devices, bolsters, mechanical
26 fastening devices, and hydraulic lift gates.

27 (d) "Rocky Mountain double" means a combination of vehicles that includes a truck tractor pulling
28 a long semitrailer and a shorter trailer."

29

-END-